

Package: spacefillr (via r-universe)

August 20, 2024

Type Package

Title Space-Filling Random and Quasi-Random Sequences

Version 0.3.3

Maintainer Tyler Morgan-Wall <tylermw@gmail.com>

Description Generates random and quasi-random space-filling sequences.

Supports the following sequences: 'Halton', 'Sobol', 'Owen'-scrambled 'Sobol', 'Owen'-scrambled 'Sobol' with errors distributed as blue noise, progressive jittered, progressive multi-jittered ('PMJ'), 'PMJ' with blue noise, 'PMJ02', and 'PMJ02' with blue noise. Includes a 'C++' API. Methods derived from ``Constructing Sobol sequences with better two-dimensional projections" (2012) <doi:10.1137/070709359> S. Joe and F. Y. Kuo, ``Progressive Multi-Jittered Sample Sequences" (2018) <https://graphics.pixar.com/library/ProgressiveMultiJitteredSampling/paper.pdf> Christensen, P., Kensler, A. and Kilpatrick, C., and ``A Low-Discrepancy Sampler that Distributes Monte Carlo Errors as a Blue Noise in Screen Space" (2019) E. Heitz, B. Laurent, O. Victor, C. David and I. Jean-Claude, <doi:10.1145/3306307.3328191>.

License MIT + file LICENSE

Imports Rcpp (>= 1.0.0)

LinkingTo Rcpp

Encoding UTF-8

RoxygenNote 7.3.1

URL <https://github.com/tylermorganwall/spacefillr>

BugReports <https://github.com/tylermorganwall/spacefillr/issues>

SystemRequirements C++17

Repository <https://tylermorganwall.r-universe.dev>

RemoteUrl <https://github.com/tylermorganwall/spacefillr>

RemoteRef HEAD

RemoteSha 0bf9644f8ff6a31576dd97b9a26a44e367899468

Contents

generate_halton_faure_set	2
generate_halton_faure_single	3
generate_halton_random_set	4
generate_halton_random_single	5
generate_pj_set	6
generate_pmj02bn_set	7
generate_pmj02_set	8
generate_pmjbn_set	9
generate_pmj_set	10
generate_sobol_owen_set	11
generate_sobol_set	12
Index	13

generate_halton_faure_set
Generate Halton Set (Faure Initialized)

Description

Generate a set of values from a Faure Halton set.

Usage

```
generate_halton_faure_set(n, dim)
```

Arguments

n The number of values (per dimension) to extract.
dim The number of dimensions of the sequence.

Value

An 'n' x 'dim' matrix listing all the

Examples

```
#Generate a 2D sample:
points2d = generate_halton_random_set(n=1000, dim=2)
plot(points2d)

#Extract a separate pair of dimensions
points2d = generate_halton_random_set(n=1000, dim=10)
plot(points2d[,5:6])

#Integrate the value of pi by counting the number of randomly generated points that fall
#within the unit circle.
pointset = matrix(generate_halton_faure_set(10000,dim=2),ncol=2)

pi_estimate = 4*sum(pointset[,1] * pointset[,1] + pointset[,2] * pointset[,2] < 1)/10000
pi_estimate
```

generate_halton_faure_single

Generate Halton Value (Faure Initialized)

Description

Generate a single value from a seeded Halton set, initialized with a Faure sequence.

Note: This is much slower than generating the entire set ahead of time.

Usage

```
generate_halton_faure_single(i, dim)
```

Arguments

i	The element of the sequence to extract.
dim	The dimension of the sequence to extract.

Value

A single numeric value representing the 'i'th element in the 'dim' dimension.

Examples

```
#Generate a 3D sample:
point3d = c(generate_halton_faure_single(10, dim = 1),
            generate_halton_faure_single(10, dim = 2),
            generate_halton_faure_single(10, dim = 3))
point3d
```

`generate_halton_random_set`*Generate Halton Set (Randomly Initialized)*

Description

Generate a set of values from a seeded Halton set.

Usage

```
generate_halton_random_set(n, dim, seed = 0)
```

Arguments

<code>n</code>	The number of values (per dimension) to extract.
<code>dim</code>	The number of dimensions of the sequence.
<code>seed</code>	Default '0'. The random seed.

Value

An 'n' x 'dim' matrix listing all the

Examples

```
#Generate a 2D sample:
points2d = generate_halton_random_set(n=1000, dim=2)
plot(points2d)

#Change the seed and extract a separate pair of dimensions
points2d = generate_halton_random_set(n=1000, dim=10, seed=2)
plot(points2d[,5:6])

#Integrate the value of pi by counting the number of randomly generated points that fall
#within the unit circle.
pointset = matrix(generate_halton_random_set(10000, dim=2), ncol=2)

pi_estimate = 4*sum(pointset[,1] * pointset[,1] + pointset[,2] * pointset[,2] < 1)/10000
pi_estimate
```

`generate_halton_random_single`*Generate Halton Value (Randomly Initialized)*

Description

Generate a single value from a seeded Halton set.

Note: This is much slower than generating the entire set ahead of time.

Usage

```
generate_halton_random_single(i, dim, seed = 0)
```

Arguments

<code>i</code>	The element of the sequence to extract.
<code>dim</code>	The dimension of the sequence to extract.
<code>seed</code>	Default '0'. The random seed.

Value

A single numeric value representing the 'i'th element in the 'dim' dimension.

Examples

```
#Generate a 3D sample:
point3d = c(generate_halton_random_single(10, dim = 1),
            generate_halton_random_single(10, dim = 2),
            generate_halton_random_single(10, dim = 3))
point3d

#Change the random seed:
#!#Generate a 3D sample
point3d_2 = c(generate_halton_random_single(10, dim = 1, seed = 10),
             generate_halton_random_single(10, dim = 2, seed = 10),
             generate_halton_random_single(10, dim = 3, seed = 10))
point3d_2
```

generate_pj_set	<i>Generate 2D Progressive Jittered Set</i>
-----------------	---

Description

Generate a set of values from a Progressive Jittered set.

Usage

```
generate_pj_set(n, seed = 0)
```

Arguments

n	The number of 2D values to extract.
seed	Default '0'. The random seed.

Value

An 'n' x '2' matrix with all the calculated values from the set.

Examples

```
#Generate a 2D sample:
points2d = generate_pj_set(n=1000)
plot(points2d, xlim=c(0,1),ylim=c(0,1))

#Generate a longer sequence of values from that set
points2d = generate_pj_set(n=1500)
plot(points2d, xlim=c(0,1),ylim=c(0,1))

#Generate a new set by changing the seed
points2d = generate_pj_set(n=1500,seed=10)
plot(points2d, xlim=c(0,1),ylim=c(0,1))

#'#Integrate the value of pi by counting the number of randomly generated points that fall
#within the unit circle.
pointset = generate_pj_set(10000)

pi_estimate = 4*sum(pointset[,1] * pointset[,1] + pointset[,2] * pointset[,2] < 1)/10000
pi_estimate
```

generate_pmj02bn_set *Generate 2D Progressive Multi-Jittered (0, 2) (with blue noise) Set*

Description

Generate a set of values from a Progressive Multi-Jittered (0, 2) (with blue noise) set.

Usage

```
generate_pmj02bn_set(n, seed = 0)
```

Arguments

n	The number of 2D values to extract.
seed	Default '0'. The random seed.

Value

An 'n' x '2' matrix with all the calculated values from the set.

Examples

```
#Generate a 2D sample:
points2d = generate_pmj02bn_set(n=1000)
plot(points2d, xlim=c(0,1),ylim=c(0,1))

#Generate a longer sequence of values from that set
points2d = generate_pmj02bn_set(n=1500)
plot(points2d, xlim=c(0,1),ylim=c(0,1))

#Generate a new set by changing the seed
points2d = generate_pmj02bn_set(n=1500,seed=10)
plot(points2d, xlim=c(0,1),ylim=c(0,1))

#Integrate the value of pi by counting the number of randomly generated points that fall
#within the unit circle.
pointset = generate_pmj02bn_set(10000)

pi_estimate = 4*sum(pointset[,1] * pointset[,1] + pointset[,2] * pointset[,2] < 1)/10000
pi_estimate
```

generate_pmj02_set *Generate 2D Progressive Multi-Jittered (0, 2) Set*

Description

Generate a set of values from a Progressive Multi-Jittered (0, 2) set.

Usage

```
generate_pmj02_set(n, seed = 0)
```

Arguments

n	The number of 2D values to extract.
seed	Default '0'. The random seed.

Value

An 'n' x '2' matrix with all the calculated values from the set.

Examples

```
#Generate a 2D sample:
points2d = generate_pmj02_set(n=1000)
plot(points2d, xlim=c(0,1),ylim=c(0,1))

#Generate a longer sequence of values from that set
points2d = generate_pmj02_set(n=1500)
plot(points2d, xlim=c(0,1),ylim=c(0,1))

#Generate a new set by changing the seed
points2d = generate_pmj02_set(n=1500,seed=10)
plot(points2d, xlim=c(0,1),ylim=c(0,1))

#'#Integrate the value of pi by counting the number of randomly generated points that fall
#within the unit circle.
pointset = generate_pmj02_set(10000)

pi_estimate = 4*sum(pointset[,1] * pointset[,1] + pointset[,2] * pointset[,2] < 1)/10000
pi_estimate
```

generate_pmjbn_set	<i>Generate 2D Progressive Multi-Jittered (with blue noise) Set</i>
--------------------	---

Description

Generate a set of values from a Progressive Multi-Jittered (with blue noise) set.

Usage

```
generate_pmjbn_set(n, seed = 0)
```

Arguments

n	The number of 2D values to extract.
seed	Default '0'. The random seed.

Value

An 'n' x '2' matrix with all the calculated values from the set.

Examples

```
#Generate a 2D sample:
points2d = generate_pmjbn_set(n=1000)
plot(points2d, xlim=c(0,1),ylim=c(0,1))

#Generate a longer sequence of values from that set
points2d = generate_pmjbn_set(n=1500)
plot(points2d, xlim=c(0,1),ylim=c(0,1))

#Generate a new set by changing the seed
points2d = generate_pmjbn_set(n=1500,seed=10)
plot(points2d, xlim=c(0,1),ylim=c(0,1))

#Integrate the value of pi by counting the number of randomly generated points that fall
#within the unit circle.
pointset = generate_pmjbn_set(10000)

pi_estimate = 4*sum(pointset[,1] * pointset[,1] + pointset[,2] * pointset[,2] < 1)/10000
pi_estimate
```

generate_pmj_set	<i>Generate 2D Progressive Multi-Jittered Set</i>
------------------	---

Description

Generate a set of values from a Progressive Multi-Jittered set.

Usage

```
generate_pmj_set(n, seed = 0)
```

Arguments

n	The number of 2D values to extract.
seed	Default '0'. The random seed.

Value

An 'n' x '2' matrix with all the calculated values from the set.

Examples

```
#Generate a 2D sample:
points2d = generate_pmj_set(n=1000)
plot(points2d, xlim=c(0,1),ylim=c(0,1))

#Generate a longer sequence of values from that set
points2d = generate_pmj_set(n=1500)
plot(points2d, xlim=c(0,1),ylim=c(0,1))

#Generate a new set by changing the seed
points2d = generate_pmj_set(n=1500,seed=10)
plot(points2d, xlim=c(0,1),ylim=c(0,1))

#Integrate the value of pi by counting the number of randomly generated points that fall
#within the unit circle.
pointset = generate_pj_set(10000)

pi_estimate = 4*sum(pointset[,1] * pointset[,1] + pointset[,2] * pointset[,2] < 1)/10000
pi_estimate
```

`generate_sobol_owen_set`*Generate Owen-scrambled Sobol Set*

Description

Generate a set of values from an Owen-scrambled Sobol set.

Usage

```
generate_sobol_owen_set(n, dim, seed = 0)
```

Arguments

<code>n</code>	The number of values (per dimension) to extract.
<code>dim</code>	The number of dimensions of the sequence.
<code>seed</code>	Default '0'. The random seed.

Value

An 'n' x 'dim' matrix with all the calculated values from the set.

Examples

```
#Generate a 2D sample:
points2d = generate_sobol_owen_set(n=1000, dim = 2)
plot(points2d, xlim=c(0,1),ylim=c(0,1))

#Generate a longer sequence of values from that set
points2d = generate_sobol_owen_set(n=1500, dim = 2)
plot(points2d, xlim=c(0,1),ylim=c(0,1))

#'#Integrate the value of pi by counting the number of randomly generated points that fall
#within the unit circle.
pointset = matrix(generate_sobol_owen_set(10000,dim=2),ncol=2)

pi_estimate = 4*sum(pointset[,1] * pointset[,1] + pointset[,2] * pointset[,2] < 1)/10000
pi_estimate
```

generate_sobol_set *Generate Sobol Set*

Description

Generate a set of values from a Sobol set.

Note: the Sobol sequences provided by spacefillr are different than those provided by randtoolbox, as spacefillr's Sobol sequences have better 2D projections (see "Constructing Sobol sequences with better two-dimensional projections" (2012) <doi:10.1137/070709359> S. Joe and F. Y. Kuo).

Usage

```
generate_sobol_set(n, dim, seed = 0)
```

Arguments

n	The number of values (per dimension) to extract.
dim	The number of dimensions of the sequence.
seed	Default '0'. The random seed.

Value

A single numeric value representing the 'i'th element in the 'dim' dimension.

Examples

```
#Generate a 2D sample:
points2d = generate_sobol_set(n=1000, dim = 2)
plot(points2d, xlim=c(0,1),ylim=c(0,1))

#Generate a longer sequence of values from that set
points2d = generate_sobol_set(n=1500, dim = 2)
plot(points2d, xlim=c(0,1),ylim=c(0,1))

#'#Integrate the value of pi by counting the number of randomly generated points that fall
#within the unit circle.
pointset = matrix(generate_sobol_set(10000,dim=2),ncol=2)

pi_estimate = 4*sum(pointset[,1] * pointset[,1] + pointset[,2] * pointset[,2] < 1)/10000
pi_estimate
```

Index

[generate_halton_faure_set](#), [2](#)
[generate_halton_faure_single](#), [3](#)
[generate_halton_random_set](#), [4](#)
[generate_halton_random_single](#), [5](#)
[generate_pj_set](#), [6](#)
[generate_pmj02_set](#), [8](#)
[generate_pmj02bn_set](#), [7](#)
[generate_pmj_set](#), [10](#)
[generate_pmjbn_set](#), [9](#)
[generate_sobol_owen_set](#), [11](#)
[generate_sobol_set](#), [12](#)